

# Viking Pro Warewash Series

Detergent, Rinse,  
& Sanitizer Control  
Systems



Visit Us Online At  
[www.thevikingbowl.com](http://www.thevikingbowl.com)



## Pro III

Powder Detergent  
and Rinse Control  
Warewash System

Viking is leading the industry with field-proven warewash systems. Viking's compact Pro Series Dispensers are backed by a solid one-year warranty. In addition to the Pro Dispensers for high-temperature probe-controlled applications, there is also a time-based Pro Probeless unit and the Pro VI for low-temperature, dump and fill, and glass washer applications.

PRO WAREWASH



## Common Applications

High and low-temperature dish machines; dump and fill dish machines; glass washers; pot and pan washers; rack, tray and cage washing machines; and laboratory bottle and test tube washing machines. See "Applications" column on back, call for feasibility of other applications.

## Pro V

Detergent, Rinse,  
& Sanitizer Warewash  
Control System

System	Dimension	Electrical	Deter. Pump Output	Deter. Solenoid	Rinse Pump Output	Sanitizer Pump Output	Low Detergent Alarm	Options	Applications	Standard Configuration
Pro I Liquid or Powder/ Solid Detergent	DL 7"H x 7"W x 6 <sup>1/2</sup> "D DP 7"H x 9 <sup>1/2</sup> "W x 6 <sup>1/2</sup> "D	A	1	Yes*	--	--	Yes	Viking Bowl, side-mount reservoir, external transformer, leg lift kit	Pot & Pan washer, cage washer, rack/tray washer, high-temp. dish machines	1 Internal Transformer
Pro II Liquid Rinse Liquid Sanitizer	7"H x 7"W x 6 <sup>1/2</sup> "D	A	--	--	2	2	--	1/4" tube, external transformer, leg lift kit	High or low-temp. rinse & sanitizer applications, glass washers, conveyor lube injector	1 Internal Transformer or 1 Internal Transformer & A Pressure Switch
Pro III Liquid Rinse Powder/Solid Detergent	7"H x 9 <sup>1/2</sup> "W x 6 <sup>1/2</sup> "D	A	--	Yes	2	--	Yes	Viking Bowl, side-mount reservoir, external transformer, leg lift kit, 1/4" tube	Pot & Pan washer, cage washer, rack/tray washer, high-temp. dish machines	2 Internal Transformers or 1 Internal Transformer & A Pressure Switch
Pro IV Liquid Rinse & Sanitizer, Liquid or Powder/Solid Detergent	7"H x 11"W x 6 <sup>1/2</sup> "D	A	1	--	2	--	Yes	External transformer, leg lift kit, 1/4" tube	Pot & Pan washer, cage washer, rack/tray washer, high-temp. dish machines	2 Internal Transformers or 2 Internal Transformers & A Pressure Switch
Pro V Liquid Rinse & Sanitizer, Liquid or Powder/Solid Detergent	DL 7"H x 11"W x 6 <sup>1/2</sup> "D DP 7"H x 9 <sup>1/2</sup> "W x 6 <sup>1/2</sup> "D	A	1*	Yes	2	2	Yes	Viking Bowl, side-mount reservoir, external transformer, leg lift kit, 1/4" rinse/sanitizer tube	Pot & Pan washer, cage washer, rack/tray washer, high-temp. dish machines	2 Internal Transformers or 2 Internal Transformers & A Pressure Switch
Pro VI One-Pump Liquid Rinse	7"H x 7"W x 6 <sup>1/2</sup> "D	B	--	--	3	--	--	1/8" Rinse Tube	Low-temp. and dump & fill dish machines	--
Pro VI Two-Pump Liquid Rinse & Detergent Only	7"H x 7"W x 6 <sup>1/2</sup> "D	B	3	--	3	--	--	1/8" Rinse Tube	Low-temp. and dump & fill dish machines	--
Pro VI Three-Pump Liquid Rinse, Sanitizer & Detergent Only	7"H x 7"W x 6 <sup>1/2</sup> "D	B	3	--	3	3	--	1/8" Rinse Tube 1/8" Sanitizer Tube	Low-temp. and dump & fill dish machines	--
Pro Probeless Liquid Rinse Powder/Solid Detergent	DL 7"H x 11"W x 6 <sup>1/2</sup> "D DP 7"H x 9 <sup>1/2</sup> "W x 6 <sup>1/2</sup> "D	B	1*	Yes	2	--	--	External transformer, 1/4" rinse tube Powder Model Viking Bowl, side-mount reservoir	High & low-temp. and dump & fill dish machines	--
Pro Glass Washer Liquid Rinse Liquid Sanitizer	7"H x 7"W x 6 <sup>1/2</sup> "D	A	--	--	2	2	--	1/8" Rinse Tube	Glass washers, low-temp. and dump & fill dish machines	1 or 2 Internal Transformers



512 Industrial Road  
Nesquehoning, PA 18240  
800.441.1343  
570.645.3633  
Fax: 570.645.3679  
sales@thevikingbowl.com

### Pump Outputs:

1. Fixed rate of 9 ounces per minute (261ml/min).
2. Adjustable rate of 1/8 to 3/4 ounce (4 to 22ml/min).  
Optional 1/4" rinse/sanitizer tube would yield an adjustable rate of 3/8 to 2 1/4 ounces (11 to 64ml/min).
3. Fixed rate of 4 ounces (116ml) per minute.

Note: All pump outputs listed are based on water. Product viscosity, and the length and rise of run may reduce actual output.

### Electrical Information

- A)** Internal transformer accepts primary voltages of 110, 208, and 240 volts AC, 50 or 60 hertz.  
**B)** Unit plugs into a 110 volt outlet. Unit can be hard wired into a 110 volt if necessary.

### Low Product Alarm

Delay adjustable from 20 seconds to 6 minutes.  
Feed is shut off during alarm condition.